

# **SUBDIVISION DESIGN GUIDELINES**

FOR

**STANFORD MEADOW**

at

**STONEBRIDGE RANCH**

## **SUBDIVISION DESIGN GUIDELINES FOR STANFORD MEADOW**

These Subdivision Design Guidelines are designed specifically for STANFORD MEADOW subdivision and are promulgated in accordance with Section 3 of Article VIII of the "Consolidated and Amended Master Declaration of Covenants, Conditions, Restrictions, Easements, Charges and Liens on and for STONEBRIDGE RANCH" (the "Master Declaration") which instrument was recorded on October 29, 1992 as Instrument No. 92-0076613 in the Public Real Estate Records of Collin County, Texas and which is incorporated herein by reference for all purposes.

The primary purpose of these Subdivision Design Guidelines is to supplement the current version of the MASTER DESIGN GUIDELINES for STONEBRIDGE RANCH. Adherence to these guidelines are intended to better assure owners of properties within the STANFORD MEADOW Subdivision that all individual improvements will conform to the same high standards of design excellence. The guidelines seek to establish a design framework which the individual homebuilder or homeowner will use as a guide for site improvement, with latitude and flexibility (on the one hand) balanced against preserving the integrity of STONEBRIDGE RANCH (on the other hand).

These Subdivision Design Guidelines will, hopefully, serve to guide, inform, aid and inspire to the same extent as they serve to prohibit, restrict and require. While some features are mandated, it should be understood that the Master Architectural Review Committee ("MARC") may make discretionary judgments to reduce or waive any requirement when it can be demonstrated (to the reasonable satisfaction of the MARC) that appropriate mitigating measures have been taken. However, such discretionary approval(s) shall not represent or constitute a binding precedent since no two or more tracts or circumstances are likely to be alike.

1. Height Limitation: Thirty-five feet (35') measured per City ordinances.

2. Minimum Dwelling Setback Requirements:

Front Yard: Twenty feet (20') to main structure.

Rear Yard: Twenty feet (20') from rear lot line to main structure (excluding accessory buildings, cabanas, decks, fences, pools, etc.).

Side Yard: Five feet (5').

Side Yard  
on Corner: Fifteen feet (15').

3. Sitework. Finished grades shall not direct concentrated water (i.e., downspouts, sub-grade drainage systems) flow onto adjacent properties and should follow the City of McKinney approved grading plans. Anytime a site is altered, it is the builder's responsibility to provide the retainage. Retaining walls are only to be constructed of stone. If side yard retaining walls are not desired, a slope of 3:1 (max.) must be achieved between the foundation slab and the side yard property line. The MARC reserves the right, upon reasonable advance notice, to require a topographical survey done by a registered surveyor before, during, or after construction.
4. Masonry. Unless otherwise specifically approved by the MARC, each single family dwelling shall have at least 75% of the vertical surfaces (excluding windows, doors and roof) composed of approved masonry. Chimneys not on a front elevation may be non-masonry. That portion of the elevation which faces the greenbelt must be 100% masonry. Lots 2 and 8-10, Block F are greenbelt lots. Same brick blends may not be used on adjacent houses (same side of street).
5. Fences Along Lakes/Greenbelts. With respect to each and every lot which has a side or rear property line coincident with or adjacent to an open space (Lots 2 and 8-10, Block F) so as to constitute "open space frontage," fences shall comply with the following requirements:
  - (A) Must be 59" (inches) in height;
  - (B) open metal, primed and painted a flat black color;
  - (C) the other standards applicable to this perimeter fence;
  - (D) constructed as indicated in the MASTER DESIGN GUIDELINES.
6. Fence Height and Materials. No fence shall exceed six feet (6') in height measured from finished grade. Except for those fences required to be constructed of open metal, all other fences shall be constructed with redwood, Western Red Cedar (#1 or "Standard and Better"). Pickets are to be placed on the exterior face or as specified by the MARC. Posts may be steel pipe columns, cedar or redwood. No pine or spruce fencing materials shall be permitted. Interior lots should have the 6'-0" height wood privacy fence.
7. Roof Drainage. In order to assist in the orderly drainage and removal of roof water and the overall quality of drainage, gutters and downspouts may be required at the discretion and direction of the MARC.
8. Roof. Any proposed composition roof materials shall be the same or equal to the 25-year dimensional shingle Tamko Elite Glass Seal (no 3-tab). The type, quality and color must otherwise be specifically approved by the MARC.
9. Required Landscaping. Per the MARC approved landscape plan, all landscape is to be installed BY THE BUILDER WITHIN THIRTY (30) DAYS of substantial completion or

change of ownership (closing). The Lot areas listed below shall be landscaped with the following size and/or number of shade trees, which shall be from the "highly recommended" or "acceptable" category described within the STONEBRIDGE RANCH Plant Palette (set forth in the Master Design Guidelines).

<u>Lot Area</u>	<u>Minimum Requirement</u>
Front Yard	One row of five (5) gallon non-deciduous (evergreen) shrubbery located along the foundation excluding porches and patios. One 4½" (min.) large canopy (i.e., red oak, live oak, cedar elm, Chinese pistachio) shade tree or one - 3" (min.) caliper shade tree with one - 1" minimum caliper ornamental tree are required for each front yard.
Adjacent to Greenbelt	One row of five (5) gallon non-deciduous (evergreen) shrubbery located along the foundation excluding porches and patios. One 4½" (min.) large canopy (i.e., red oak, live oak, cedar elm, Chinese pistachio) shade tree per rear yard, to be located within ten feet (10') of the rear property line.
Corner/Side Yard	A total of one (1) 2½" caliper shade tree is required to face the side street. One row of non-deciduous (evergreen) five (5) gallon shrubbery is required where the foundation is exposed to the street. Where 6' solid wood fences run along the street frontage, one row of evergreen five (5) gallon shrubs is required.
AC Units/Mechanical Equipment Meters	One row of non-deciduous (evergreen) five gallon (min.) shrubbery is required to screen these elements from public view.

9. Irrigation. Unless viewed from a greenbelt, common space, golf course, or public road, the MARC encourages but does not require that each Lot have an automatic irrigation system. Each Lot which has a rear or side yard adjoining a Greenway Frontage area (e.g. golf course, lake, park, greenbelt, open area) must have an automatic irrigation system installed within such area concurrent with the finishing stages of the residential dwelling and the plans and specification to be submitted to the MARC must show the proposed irrigation arrangement. All automatic irrigation systems shall be designed to have overlapping coverage. Controller devices must be located inside the garage.

10. Sidewalks. Unless otherwise approved by the MARC the builder of each single-family home shall construct, install and provide a public sidewalk per the attached Sidewalk Plan ("Exhibit A") which shall: (a) be approved (as to size, location and materials) by the MARC; (b) comply with applicable City of McKinney, Texas standards; (c) incorporate a "lay-down" curb on corner lots or other similar lots designated by the MARC; and (d) to the extent applicable, conform to and continue the hike-and-bike trail within STONEBRIDGE RANCH. All concrete sidewalks, driveways, walkways and entry paths which are within the public right-of-way shall be broom finished.
11. Elevations. As a general rule or objective, each floor plan should have three (3) elevations. Elevations are allowed to repeat when there are three (3) intervening lots of separation along the fronting or side/corner streets.
12. Paint Colors. The trim colors of the house will be limited to a specific color family complimentary of the masonry selection. Garage doors should be painted a subtle variation of the primary house color. All exposed exterior flashing is to be painted a color to match the masonry color. Roof vents are to be painted a color to match the roof color.
14. Homebuilder Construction. Please refer to the most recent publication of the Construction Site Policy (attached).

## REVISION LOG

### STANFORD MEADOW

[illegible]

06/18/2015