


# **SUBDIVISION DESIGN GUIDELINES**

FOR

**WREN CREEK  
PHASE II-B**

at

**STONEBRIDGE RANCH**



06/18/2015

**SUBDIVISION DESIGN GUIDELINES  
FOR  
WREN CREEK PHASE II-B**

These Subdivision Design Guidelines are designed specifically for WREN CREEK PHASE II-B subdivision and are promulgated in accordance with Section 8.5 of Article VIII of the "First Amended and Restated Master Declaration of Covenants, Conditions and Restrictions for STONEBRIDGE RANCH" (the "Master Declaration") which instrument was recorded on December 5, 2000 as Instrument No. 2000-0132145 in the Public Real Estate Records of Collin County, Texas and which is incorporated herein by reference for all purposes.

The primary purpose of these Subdivision Design Guidelines is to supplement the current version of the MASTER DESIGN GUIDELINES for STONEBRIDGE RANCH. Adherence to these guidelines are intended to better assure owners of properties within the WREN CREEK PHASE II-B Subdivision that all individual improvements will conform to the same high standards of design excellence. The guidelines seek to establish a design framework which the individual homebuilder or homeowner will use as a guide for site improvement, with latitude and flexibility (on the one hand) balanced against preserving the integrity of STONEBRIDGE RANCH (on the other hand). These Subdivision Design Guidelines will, hopefully, serve to guide, inform, aid and inspire to the same extent as they serve to prohibit, restrict and require. While some features are mandated, it should be understood that the Master Architectural Review Committee ("MARC") may make discretionary judgments to reduce or waive any requirement when it can be demonstrated (to the reasonable satisfaction of the MARC) that appropriate mitigating measures have been taken. However, such discretionary approval(s) shall not represent or constitute a binding precedent since no two or more tracts or circumstances are likely to be alike.

1. Height Limitation

Thirty-five feet (35') measured from grade.

2. Minimum Dwelling Setback Requirements:

Front Yard: Twenty feet (20') to main structure.

Rear Yard: Twenty feet (20') from rear lot line to main structure (excluding accessory buildings, cabanas, decks, fences, pools, etc.) unless adjacent to lake or other water body which might permit a less restrictive setback to be approved by the MARC.

Side Yard: Five feet (5').

Side Yard  
on Corner: Fifteen feet (15').

Driveway: Driveway pavement shall be set back a minimum of 1'-6" from the property line. In retaining wall situations on side lot lines, the driveway may abut the retaining wall on the high side as long as the retaining wall creates a raised curb effect along the driveway.

3. Sitework. Finished grades shall not direct concentrated water (i.e., downspouts, pool overflows, sub-grade drainage systems) flow onto adjacent properties and should follow the City of McKinney approved grading plans. Anytime a site is altered, it is the builder's responsibility to provide the retainage. Retaining walls are only to be constructed of brown Hackett stone. If side yard retaining walls are not desired, a maximum slope of 3:1 must be achieved between the foundation slab and the side yard property line. The MARC reserves the right, upon reasonable advance notice, to require a topographical survey done by a registered surveyor before, during, or after construction.
4. Masonry. Only chimneys on the front elevation or on a side elevation within 10' of the front elevation must be 100% masonry. Identical brick blends may not occur next door to each other along the fronting street. Elevations, including chimneys, which face the greenbelt/common area and/or Stonebridge Drive, including Block C, Lots 1-11 and 18; Block D, Lots 1-16 and 28; and Block E, Lot 7-15, must be 100% masonry. Except as specifically stated in this section, other chimneys may be non-masonry.
5. Fences for Interior Lots. Unless otherwise approved by the MARC, no fence shall exceed six feet (6') in height measured from finished grade. Except for those fences required to be constructed of metal, all other fences shall be constructed with Western Red Cedar (#1 or "Standard and Better") with pickets placed on the exterior face or as specified by the MARC. Posts may be steel pipe columns or cedar. No pine or spruce fencing materials shall be permitted. Interior lots should have a 6'-0" height solid wood privacy fence.
6. Fences Along Greenbelts/Common Areas. With respect to each and every lot which has a side or rear property line coincident with or adjacent to a greenbelt/common area so as to constitute "greenbelt/common area frontage," including Block C, Lot 18; Block D, Lots 5-16 and 28; and Block E, Lots 7-15, fences and walls along the frontage shall comply with the following requirements:
  - (A) 59" in height from bottom of the lower horizontal rail to top of the pickets;
  - (B) tubular metal, primed and painted a flat black color; and
  - (C) constructed as indicated in the MASTER DESIGN GUIDELINES (titled "Required Metal Fence Elevation At Golf Courses, Lakes, and Open Spaces").

Fences along the side yard shall be the 6' cedar fence as indicated in the Master Design Guidelines.

7. Roof Drainage. In order to assist in the orderly drainage and removal of roof water and the overall quality of drainage, gutters and downspouts may be required at the discretion and direction of the MARC.
8. Roof. Any proposed composition roof materials shall be the same as or equal to the 25 year Tamco Elite Glass Seal and shall "weigh" a minimum of 230 lbs. per square. The type, quality and color must otherwise be specifically approved by the MARC.
9. Required Landscaping. Per the MARC approved landscape plan, all landscape is to be installed BY THE BUILDER WITHIN THIRTY (30) DAYS of substantial completion or change of ownership (closing). The Lot areas listed below shall be landscaped with the following size and/or number of shade trees, which shall be from the "highly recommended" or "acceptable" category described within the STONEBRIDGE RANCH Plant Palette (set forth in the Master Design Guidelines).

Lot Area

Minimum Requirement

Front Yard

One row of five-gallon (min.) evergreen shrubs planted at a maximum spacing of 3'-0" o.c. and located along the foundation excluding porches and patios. A total of one - 2½" caliper (min.) large canopy (i.e., red oak, live oak, cedar elm, Chinese pistachio) shade tree is required for each front yard. In addition to the one tree previously mentioned, 1" caliper (min.) ornamental tree (if multi-trunk, the total of all trunks shall be 1") is required.

Adjacent to Greenbelt/  
Common Area (including  
Block C, Lot 18; Block D,  
Lots 5-16, and 28; and  
Block E, Lots 7-15

One row of five-gallon (min.) evergreen shrubs planted at a maximum spacing of 3'-0" o.c. and located along the foundation excluding porches and patios. A total of one - 2½" caliper (min.) large canopy (i.e., red oak, live oak, cedar elm, Chinese pistachio) shade tree per rear yard, to be located within ten (10') feet of the rear property line.

Corner Yard

A total of one 2½" caliper (min.) shade tree is required to face the "side" street and be located in the side yard (outside the fenced portion of the yard). One row of five-gallon (min.) evergreen shrubs planted at a maximum spacing of 3'-0" o.c. is required where the foundation is exposed to the street.

Where six foot (6') solid wood fences run along the street frontage, one row of five gallon (min.) evergreen shrubs planted at a maximum spacing of 3'-0" o.c. is required.

AC Units/Mechanical  
Equipment Meters

One row of five-gallon (min.) evergreen shrubs planted at a maximum spacing of 3'-0" o.c. is required to screen these elements from public view.

10. Irrigation. The MARC encourages, but does not require, that each Lot have a front-yard automatic irrigation system.
11. Sidewalks & Driveways. Unless otherwise approved by the MARC the builder of each single-family home shall construct, install and provide a public sidewalk which shall: (a) be approved (as to size, location and materials) by the MARC; (b) comply with applicable subdivision improvement plan and other City of McKinney, Texas standards; (c) incorporate a "lay-down" curb on corner lots or other similar lots designated by the MARC; and (d) to the extent applicable, conform to and continue the hike-and-bike trail within STONEBRIDGE RANCH. Concrete flatwork which is within the public right-of-way must be broom finished.
12. Elevations. As a general rule or objective, each floor plan should have three (3) elevations. Elevations shall not repeat along the fronting or siding streetscape without at least 2 intervening homes of sufficient dissimilarity (both sides of the street). The intent of this guideline is to avoid the negative "look alike" effect of frequent repetition, while allowing sufficient latitude for the builder in satisfying market demand.
13. Paint Colors. The trim colors of the house will be limited to a specific color family complimentary of the masonry selection. Garage doors should be painted a subtle variation of the primary house color. All exposed exterior flashing is to be painted a color to match the masonry color. Roof vents are to be painted a color to match the roof color.
14. Mailboxes. All mailboxes are to be located within a masonry structure to match the main house on the Lot and approved by the MARC. Mailboxes on adjacent Lots should be grouped in pairs on the property line (side by side, not two mailboxes in one structure) as

much as possible. Height should be 42"-44" from the surface of the street to the bottom of the mailbox. The front should be even with the curb. The red flag should be attached to the right side of the mailbox. Construction traffic should never block access to mailboxes of occupied homes.

15. Homebuilder Construction. Please refer to the most recent publication of the Construction Site Policy.

## SUBDIVISION DESIGN GUIDELINES REVISION LOG WREN CREEK PHASE II-B

[illegible]

06/18/2015

Filed and Recorded  
Official Public Records  
Stacey Kemp  
Collin County, TEXAS  
04/16/2007 08:56:39 AM  
\$64.00 TFOSTER  
20070416000505260



*Stacey Kemp*